

【php】在 CentOS 6 安裝、設定 Oracle PDO_OCI

在 CentOS 6 安裝、設定 Oracle PDO_OCI | 未知 (dtask.idv.tw)

<https://www.oracle.com/database/technologies/instant-client.html>

```
<?php
// IP 與 PORT
$tns = '
(DESCRIPTION =
  (ADDRESS_LIST =
    (ADDRESS = (PROTOCOL = TCP)(HOST = 192.168.3.1)(PORT = 1521))
  )
  (CONNECT_DATA =
    (SERVICE_NAME = orcl)
  )
)';

$user = 'tnfd'; // 帳號
$passwd = 'tnfd'; // 密碼

try {
    $dbConn = new PDO('oci:dbname=' . $tns, $user, $passwd);
} catch (PDOException $e){
    echo $e->getMessage();
}

$stmt = $dbConn->query('SELECT * FROM BACUST00');
$row = $stmt->fetch();

echo '<pre>';
var_dump($row);
echo '</pre>';
```

```
export ORACLE_HOME=/usr/lib/oracle/11.2/client64
export ORACLE_BASE=/usr/lib/oracle/11.2
export LD_LIBRARY_PATH=$ORACLE_HOME/lib:$LD_LIBRARY_PATH
export PATH=$ORACLE_HOME/bin:$PATH
```

🕒 修訂版本 #3

★ 由 treeman 建立於 1 🕒 2022 17:26:41

🔧 由 treeman 更新於 5 🕒 2023 10:14:59