

# 【shell】內建變數

\$BASH_ENV	absolute path of startup file
\$CDPATH	directories searched by cd
\$FCEDIT	absolute path of history editor
\$HISTCMD	the history number of the current command
\$HISFILE	absolute path of history file
\$HISTSIZE	number of remembered commands
\$HOME	login directory
\$IFS	token delimiters
\$LINENO	current line number in shell script
\$LINES	terminal height
\$MAIL	absolute path of mailbox
\$MAILCHECK	number of seconds to check mail
\$OLDPWD	absolute path of previous directory
\$OPTARG	option set by getopt
\$OPTIND	option's ordinal position set by getopt
\$OSTYPE	the OS on which bash is executing
\$PATH	command search path
\$PPID	process ID of parent
\$PS1	primary prompt
\$PS2	secondary prompt
\$PWD	absolute path of current directory
\$RANDOM	random integer
\$REPLY	default variable for read
\$SECONDS	number of seconds since shell started
\$SHELL	absolute pathname of preferred shell
\$TMOUT	seconds to log out after lack of use
\$UID	user ID of the current user
\$\$	process ID of current shell
\$?	exit status of most recent statement
\$#	參數的數目
\$*	代表所有參數
\$!	PID of the most recently started backgroup job

🕒 修訂版本 #1

★ 由 treeman 建立於 9 🕒 2022 01:09:42

✍ 由 treeman 更新於 10 🕒 2024 15:22:45